



HONEYWELL INDOOR DOME CAMERA



Honeywell's HD3 indoor mini-dome cameras encompass the latest in colour Digital Signal Processing (DSP) technology. The HD3 integrates a camera and lens into a one-piece, tamper proof, compact unit that can be surface or flush mounted for fast and easy installation. It is attractive and unobtrusive yet provides a crime-detering presence round-the-clock with its excellent low light imaging protection. A service/monitor cable is also included for easy on-site adjustments and the housing is designed to mount directly to a ceiling or wall.

The HD3 is a Super High Resolution Colour camera incorporating a 1/3" CCD and come equipped with a 2.8 – 10 mm (F1.3) Vari-focal Auto Iris lens to cover a wide range of viewing angles. Picture adjustment after installation is easy thanks to the 3-dimensional gimbal that is capable of 360° of pan, 180° of tilt and 360° of horizontal rotation. The HD3 also features a tamper resistant, lockable cover and a "cable management" housing design for installations that require the video and power connectors to be contained within the housing base.

It accepts either 12 VDC or 24 VAC (auto sensing) for proper operation and flexible installation. The Automatic Backlight Compensation (BLC) and Auto Tracking White Balance (ATW) ensure crisp color images in dark or backlit environments, such as windows and doorways. The Automatic Gain Control (AGC) feature increases the signal strength from the camera when scene lighting is low, keeping the picture sharp and viewable.

Features

- 1/3" Sony Interline CCD
- Single model for surface mount and recessed ceiling applications, 4S adapter plate also supplied
- Tamper resistant dome offers secure installation
- Polycarbonate housing and dome
- Easy to use "cable management" housing design
- Clear dome with liner for discreetness with no light loss
- Model - HD3 Super High Resolution colour: 540 TV lines
- 2.8 – 10 mm (F1.3) Vari-focal Auto Iris lens
- Models available in off white or black
- Local video output for setup
- 3-D Axis gimbal
- Line lock with phase adjustment (24 VAC)
- Dual 12 VDC/24 VAC voltage
- Pendant and wall mount kit available